

550VX

VACUUM EXCAVATOR SERIES



550VX model shown.

FEATURES

- » Patented Viper Pothole Tool available – the fastest, cleanest, easiest-to-use pothole gun in its class.
- » Power by CAT – unexcelled performance and reliability.
- » Vacuum pump blowers by Gardner Denver – rugged and high performance.
- » Premium silencer package – reduced noise complaints.
- » Compact low profile – good visibility for your driver and stability in rough locations.
- » Rugged construction the way a contractor needs it – heavy duty frames and largest axle capacity in its class.
- » Balanced design with optimum tongue weight – easy on your trucks.
- » Narrowest machine in it's class makes it maneuverable and easy to see around.
- » Reverse flow is standard – fast tank emptying, blow obstructions out of vacuum hose and backflush the filters for quick-easy cleaning.
- » Unique single handle door latch design for easier, faster opening and closing, power door lock available.

AN IDEAL MACHINE FOR

- » Potholing – safely dig test holes in the ground to locate buried utilities for horizontal directional drills.
- » Safe utility locating and/or daylighting.
- » Clean out storm drains, catch basins and valve boxes.
- » Cleaning up drilling fluids and mud.
- » General construction site cleanup.
- » Keyholing or utility microsurgery.
- » Environmental cleanup – everything from hurricane aftermath to oil spills.
- » Slot trenching.

550VX VACUUM EXCAVATOR SERIES

FEATURES	550VLX	550VX STD CFM	550VX HI CFM
Mountings	Trailer, truck & skid mounting	Trailer, truck & skid mounting	Trailer, truck & skid mounting
Spoils Capacity (gallons / liters)	550 gallons / 2,082 liters	550 gallons / 2,082 liters	550 gallons / 2,082 liters
Water Capacity (gallons / liters)	2 x 100 gallons / 2 x 378 liters	2 x 100 gallons / 2 x 378 liters	2 x 100 gallons / 2 x 378 liters
Optimum & Balanced Tongue Weight	454 lbs	544 lbs	544 lbs
Engine	31 Hp OHV Twin air-cooled gasoline	42 Hp CAT Industrial diesel; Tier 4i	50 Hp CAT Industrial diesel; Tier 4i
Fuel Tank Capacity (gallons / liters)	8 gallons / 30 liters	29 gallons / 110 liters	29 gallons / 110 liters
Dual LED work lights and strobe	Optional	Standard	Standard
Warranty	One Year	One Year	One Year

OPERATOR CONTROLS

Controls Location	Front curbside with lockable cabinet	Front curbside with lockable cabinet	Front curbside with lockable cabinet
Hour Meter / Tachometer / Vacuum Gauge	Optional	Standard	Standard
Water Supply Reel	Rear Curbside	Rear Curbside	Rear Curbside
Load Level Indicator and Auto Shutoff	Auto Shutoff	Sight Glass & Auto Shutoff	Sight Glass & Auto Shutoff
Reverse Flow	Available	Standard	Standard

SPOILS TANK DETAILS

Hydraulic Hoist Unload	Twin cylinder	Twin cylinder	Twin cylinder
Full Opening Rear Door	Hydraulically operated	Hydraulically operated	Hydraulically operated
Rear Door Latch	Manual, power door lock available	Manual, power door lock available	Manual, easy to power door lock available
Inlet Valve Size / Drain Valve Size	4" / 6"	4" / 6"	4" / 6"

TRAILER DETAILS - HEAVY DUTY 6" C-CHANNEL FRAME

Trailer/Hitch Type	Tandem Axle / Pintle	Tandem Axle / Pintle	Tandem Axle / Pintle
Height x Length x Width (feet / inches)	78" x 15'8" x 81"	85" x 19'6" x 81"	85" x 19'6" x 81"
Empty Weight - lbs / kg	5,990 lbs / 2711 kg	6,080 lbs / 2758 kg	6,200 / 2812 kg
Gross Vehicle Weight Rating (lbs / kg)	9,990 lbs / 4531 kg	12,800 lbs / 5806 kg	13,000 lbs / 5898 kg
Axles, Capacity and Suspension Type	2 x 6,000 lbs Torsion	2 x 6,000 lbs Torsion	2 x 6,000 lbs Torsion
Tire Size	ST235/80 R 16 Load Range E	ST235/80 R 16 Load Range E	ST235/80 R 16 Load Range E
Trailer Brakes	Never adjust electric	Never adjust electric	Never adjust electric

VACUUM PUMP / BLOWER DETAILS

Vacuum Pump/Blower Type	Positive displacement lobe pump	Positive displacement lobe pump	Positive displacement lobe pump
CFM / Max Hg	600 CFM / 15" / Gardner Denver Blower	600 CFM / 15" / Gardner Denver Blower	1000 CFM / 15" / Gardner Denver Blower
Reverse Flow	Available	Standard	Standard
Cyclo-Separator Air Filter Type / Capacity	Cyclo-Separator with 3 micron filter, 12,000 sq in capacity	Cyclo-Separator with 3 micron filter, 12,000 sq in capacity	Cyclo-Separator with 3 micron filter, 17,000 sq in capacity

WATER SYSTEM DETAILS

Electronic Low Water Shut-Off	Standard	Standard	Standard
Auto Water Pump Unloader to Reduce Engine Loading & Wear	Standard	Standard	Standard
Water Pump Drive	Belt w/ Electric Clutch	Belt w/ Electric Clutch	Belt w/ Electric Clutch
Water Supply Hose	50' x 3/8" ID	50' x 3/8" ID	50' x 3/8" ID
Easy-to-Use Winterize System	Standard	Standard	Standard

OPTIONS

Patented Cyclo-Jet Pothole Excavator – Stainless or Dielectric	Available	Recommended	Recommended
Curbside Remote Auxiliary Hydraulics	Optional	Optional	Optional
Full Hydraulic Remote Controlled Boom or Manual Boom	Optional	Optional	Optional
Lighted Arrow Bar to Direct Traffic	Optional	Optional	Optional
Removable Water Heater	Optional	Optional	Optional
4" - 6" Vac Hose Upgrade	Available on HiCFM only	Available on HiCFM only	Optional
In Tank Clean Out System	Optional	Optional	Optional
Spin Doctor Valve Exerciser – Mounted with Required Extenders	Optional	Optional	Optional
Sewer Jetter	Not Available	Optional	Optional