



275

812 West 10th Pella, Iowa 50219

www.ring-o-matic.com

THE INNOVATOR - NOT The Immitator!



Standard Equipment

Enclosed 34 HP Liquid Cooled OHV Gas Engine
Curbside Control Panel
450 CFM @ 14" Hg. Direct Drive Lobe Type Blower
Large Silencer, Blower Muffler For Noise Abatement Of Vacuum Pump
3" Four Position Cast Iron Vacuum-Pressure Valve
2" Pressure Relief Valve
Cat High Pressure Water Pump w/ Electric Clutch – 5.5 GPM @ 3500 PSI
Low Water Emergency Siren
1" Fresh Water Filter With #40 Mesh Screen
Cat Pressure Sensitive Regulating Unloader Valve
10 Gal. FHWA Approved Steel Gas Tank
100 Gal. Fresh Water Tank with 1 1/2" Drain Valve
275 Gal. Spoils Tank
6" Full Spoils Tank Check Valve
20" Manway and Pressurized Discharge
1 – 6000# Torflex Rubber Torsion Axle
2 - LT245/75 R16 Load Range E Tires
12 Volt Battery
5 Micron Washable Bag Filtration, Wet or Dry Vacuum Capability, 3" Drain Valve
1 – 2 1/2" Vacuum Relief Valve
1 – 2 1/2" Stainless Steel Vacuum Gauge
1 – 2 1/2" Stainless Steel Pressure Gauge
25' – 3" Suction Hose

Lockable Hose Reel w/ 50' HP Hose & Flexible Spray Wand With Nozzle Protector
Patented 3" Stainless Steel Emulsifier w/ Rotary Laser Turbo Nozzle – 5'
16" Lawn Sweep On 3" Steel Tube
Pintel Hitch
Optional - Strobe & Dual Halogen Work Light Kit
Optional - 37 HP Liquid Cooled Deutz Diesel Engine
Optional - Anti-Siphon Kit

Tongue Weights

Unit Empty: 680#
Full 100 Gal. Water Tank: 740#
Total Dry Weight: 2,740#

Dimensions

Height: 78"
Width: 63"
Length: 14'
GVWR: 6000#

For information or to find a dealer near you, contact:

Mike Schippers at 1-800-544-2518